

(12) UK Patent Application (19) GB (11) 2 334 301 (13) A

(43) Date of A Publication 18.08.1999

(21) Application No 9803341.8

(22) Date of Filing 17.02.1998

 (71) Applicant(s)
 Telefonaktiebolaget L M Ericsson
 (Incorporated in Sweden)
 S-126 25, Stockholm, Sweden

 (72) Inventor(s)
 Roger Charles James Enright

 (74) Agent and/or Address for Service
 Haseltine Lake & Co
 Imperial House, 15-19 Kingsway, LONDON,
 WC2B 6UD, United Kingdom

 (51) INT CL⁶
 E05D 1/04 7/00, H04M 1/02

 (52) UK CL (Edition Q)
 E2F FAA FCD
 H4J JK J36Q

 (56) Documents Cited
 GB 2289595 A GB 2179500 A EP 0776140 A1
 US 5661641 A

 (58) Field of Search
 UK CL (Edition P) E2F FAA FCD FCP, H4J JK
 INT CL⁶ E05D 1/00 1/04 3/02 7/00, H04B 1/38, H04M
 1/02
 Online: WPI

 (54) Abstract Title
Slidable and rotatable hinge assembly for a mobile radiotelephone

(57) A combination radiotelephone and electronic organiser/portable computer device comprises a first housing 2 and a second housing 4 which is mounted on the first housing using a pinless hinge assembly 12. The hinge assembly comprises the curved edge of the first housing which receives a pin formed integrally with the second housing. This allows the second housing to be linearly slidable with respect to the first housing from a closed position of the device to a first open position of the device to allow operation of the radiotelephone. In addition, the second housing is rotatable with respect to the first part, from the closed position to a second open position of the device for operation of the electronic organiser/portable computer.




FIG. 2








FIG. 3








FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

HINGE ASSEMBLIES FOR ELECTRONIC DEVICES

The present invention relates to hinge assemblies for use with electronic devices. For example, but not exclusively, the present invention relates to hinge assemblies for mobile telephones and portable computers.

DESCRIPTION OF THE RELATED ART

Many current mobile telephones make use of a hinged cover, or "flip", to enable the size of the telephone to be kept desirably small and to protect the display and keypad of the telephone when not in use. Similarly, portable computers/electronic organisers make use of hinged cases to enable a small size of device to be produced, as well as to provide protection for display and keypad components.

[Do you have any examples of current designs of hinge assemblies for mobile phones that could give a similar function as the invention?]

However, previously considered hinge assembly designs do not readily allow a mobile telephone to include portable computer/electronic organiser functions, whilst retaining the small size and ability to protect components of current separate mobile telephones and organisers.

SUMMARY OF THE PRESENT INVENTION

According to a first aspect of the present invention, there is provided an electronic device comprising a first housing and a second housing which is mounted on the first housing by way of a hinge assembly, wherein the hinge assembly comprises:

first and second cooperating parts of said first and second housings respectively,

the second part being rotatably and slidably engaged with the first part, such that the second

housing is linearly movable, with respect to the first housing, from a closed position of the device to a first open position of the device, and such that the second housing is rotatable, with respect to the first part, from the closed position to a second open position of the device.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a mobile telephone including a hinge assembly embodying one aspect of the present invention, in a closed position;

Figure 2 shows the mobile telephone of Figure 1 in a first open position;

Figure 3 shows the mobile telephone of Figure 1 in a second open position;

Figures 4 and 5 show perspective and end views respectively of a first housing of the telephone of Figure 1;

Figures 6 and 7 show perspective and end views respectively of a second housing of the telephone of Figure 1;

Figure 8 shows a side elevation of the housing of Figures 6 and 7;

Figure 9 shows a partial end cross-sectional view of the housings of the telephone of Figure 1.

DETAILS OF THE DESCRIPTION OF THE PREFERRED EMBODIMENT

A mobile telephone 1 is shown in Figure 1 in a closed position, and comprises first and second housings 2 and 4 which are movably attached to one another by way of a hinge assembly 12.

In this example, the first housing 2 carries a battery 10 and an antenna 14. The second housing member carries a keypad 6 for user input, and a microphone 8.

In the closed position shown in Figure 1, the

second housing 4 covers the whole of an upper face of the first housing 2, and is held in place by way of a clip 16. In this condition, the telephone is sealed, and the internal components of the telephone are protected from damage.

A first open position of the telephone is shown in Figure 2, in which the telephone has the usual functions of a mobile telephone, ie. sending and receiving telephone calls. To enable such use, the second housing, or cover, 4 is moved along the housing 2, so that a telephone display 9, and a loudspeaker 7 are revealed for use in conventional manner by the user of the telephone. In one embodiment of the invention, the movement of the cover 4 can automatically cause the telephone to answer an incoming call, or to be put into a dialling mode (ie. an "off-hook" condition).

Figure 3 shows a second open position of the telephone, in which the cover 4 has been opened, from the closed position of Figure 1, about the hinge assembly 12, to reveal fully the display 9 carried by the main housing 2. The cover 4 can carry on its inner surface an input device, for example a touch sensitive scribble pad, to enable a user of the device to input data. In the example shown, speakers 18 and 19 are provided in the main housing 1 for relaying audio information to the user. In this second open position, the mobile telephone can be used as a portable computer/electronic organiser. For example, the input device can be used to input text for downloading to an office computer, or the device could be used to send facsimile message by making use of the mobile telephone functions.

The hinge assembly 12 is shown in greater detail in Figures 4 to 9.

Referring to Figure 4 and 5, the first housing 2 of the telephone carries a first part 121 of the hinge

assembly 12. This first part 121 extends along at least part of one side edge region of the housing 2 by way of a connecting portion 124. The first part 121 curves from the front edge region towards the rear edge region of one side of the telephone, thereby defining a curved internal surface 125. The curved surface 125 is for engagement with a second part of the hinge as will be described below.

The curved surface 125 carries a number of contacts 241 for providing power and function control for the telephone. The contacts are intended to connect with corresponding contacts on the second part of the hinge assembly 12.

Figure 6 shows a perspective view of the second housing 4, and Figure 7 shows an end view thereof. The second housing 4 carries a substantially cylindrical elongate second part 122 which forms the hinge pin of the hinge assembly 12. The second part 122 extends along on edge region of the second housing 4, and defines a curved external surface for engagement with the curved internal surface of the first part 121. The second part 122 carries, on the outer surface thereof, contacts 242 which are for connecting with the contacts 241 carried by the first part 121. The second part is also provided with a stop 28 for preventing excessive rotation between the two housings,

The electrical connections made by the contacts 241 and 242 are dependent upon the relative positions of the first and second housings 2 and 4, and are preferably used to determine the function of the device (ie. a mobile telephone, or portable computer). The contacts 241 and 242 can also be used for power transfer between the two housings 2 and 4 in the two open positions. In addition, a contact can be specifically provided to initiate changes in function of the telephone when the housings 2 and 4 are moved

between the two open positions. The contacts can also be used for the transfer of data between components in the two housings 2 and 4.

5 In order to hold the two housings 2 and 4 in place in the various positions, the first housing 2 is provided with a clip arrangement 16, and the second housing 4 is provided with two stop members 31 and 32. These stop members are shown in Figures 8 and 9.

10 As shown in Figure 9, a first stop member 31 is engaged with the clip 16. The clip 16 is biased to engage with the stop member concerned by way of a spring device 161. In order to release the second housing 4 from the closed position of the device, the clip 16 is pressed into the first housing 2, thereby
15 releasing the stop member 31. The second housing 4 can then be moved along the first housing 2 until the second stop member 32 engages with the clip 16. The device is then held in the first open position.

20 Similarly, the clip 16 must be depressed so that the second housing 4 can be rotated about the hinge 12 in order to provide the second open position of the device.

CLAIMS

1. An electronic device comprising a first housing and a second housing which is mounted on the first housing by way of a hinge assembly, wherein the
5 hinge assembly comprises:

first and second cooperating parts attached to the first and second housings respectively,

the second part being rotatably and slidably engaged with the first part, such that the second
10 housing is linearly movable, with respect to the first housing, from a closed position of the device to a first open position of the device, and such that the second housing is rotatable, with respect to the first part, from the closed position to a second open
15 position of the device.

2. A device as claimed in claim 1, wherein the first part of the hinge assembly is provided by a first elongate member which extends along an edge region of the first housing of the device, and which defines a
20 first surface extending along the first part, and wherein the second part of the hinge assembly is provided by a second elongate member which extends along an edge region of the second housing, and which defines a second surface, the second elongate member
25 being engaged with the first elongate member such that at least part of the first surface is in contact with the second surface.

3. A device as claimed in claim 2, wherein the first and second surfaces carry electrical contacts for
30 establishing electrical connections between the first and second housings in dependence upon the relative position of the first housing with respect to the first housing.

4. A device as claimed in claim 2 or 3, wherein
35 the first surface is an internal concave curved surface, and the second surface is a corresponding

external convex curved surface, the second part of the hinge assembly being at least partially held within the first part.

5 5. A device as claimed in any one of claims 2, 3 or 4, wherein the first and second housings carry respective cooperating parts of a clip mechanism for holding the housings in a desired one of the closed, first and second open positions.

10 6. An electronic device substantially as hereinbefore described with reference to, and as shown in, the accompanying drawings.

Amendments to the claims have been filed as follows

1. An electronic device comprising a first housing and a second housing which is mounted on the first housing by way of a hinge assembly, wherein the hinge assembly comprises:

5 first and second cooperating parts attached to the first and second housings respectively, the second part being rotatably and slidably engaged with the first part, such that the second housing is rotatable with respect to the first part, about an axis from the closed position to a first open position of the device, and such that the second housing is linearly movable, with respect to the first housing, in a direction parallel to the axis, with respect to the first housing, from a closed position of the device to a second open position of the device.

2. A device as claimed in claim 1, wherein the first part of the hinge assembly is provided by a first elongate member which extends along an edge region of the first housing of the device, and which defines a first surface extending along the first part, and wherein the second part of the hinge assembly is provided by a second elongate member which extends along an edge region of the second housing, and which defines a second surface, the second elongate member being engaged with the first elongate member such that at least part of the first surface is in contact with the second surface.

3. A device as claimed in claim 2, wherein the first and second surfaces carry electrical contacts for establishing electrical connections between the first and second housings in dependence upon the relative position of the first housing with respect to the first housing.

4. A device as claimed in claim 2 or 3, wherein the first surface is an internal concave curved

surface, and the second surface is a corresponding external convex curved surface, the second part of the hinge assembly being at least partially held within the first part.

5 5. A device as claimed in any one of claims 2, 3 or 4, wherein the first and second housings carry respective cooperating parts of a clip mechanism for holding the housings in a desired one of the closed, first and second open positions.

10 6. An electronic device substantially as hereinbefore described with reference to, and as shown in, the accompanying drawings.



The Patent Office

10

Application No: GB 9803341.8
Claims searched: 1-6

Examiner: Paul Foot
Date of search: 7 May 1998

Patents Act 1977 Amended Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.P): E2F: FAA, FCD, FCP
H4J: JK

Int Cl (Ed.6): E05D: 1/00, 1/04, 3/02, 7/00
H04B: 1/38
H04M: 1/02

Other: Online: WPI

Documents considered to be relevant:

| Category | Identity of document and relevant passage | Relevant to claims |
|----------|---|--------------------|
| X | GB2289595A (NEC) See esp. figs. 3A - 4C | 1 |
| X | GB2179500A (STROMBERG GREEST) Whole document relevant | 1, 2, 4 |
| A | EP0776140A1 (NOKIA) See esp. figs. 2 & 3 | |
| X | US5661641A (SHINDO) Whole document relevant | 1 |

| | | | |
|---|---|---|--|
| X | Document indicating lack of novelty or inventive step | A | Document indicating technological background and/or state of the art. |
| Y | Document indicating lack of inventive step if combined with one or more other documents of same category. | P | Document published on or after the declared priority date but before the filing date of this invention. |
| & | Member of the same patent family | E | Patent document published on or after, but with priority date earlier than, the filing date of this application. |